

One-Light Outdoor

Project:

Fixture Type: Location:

Contact:

Images:

Wall mounted • Wet location listed PROGRESS LED



P6076-3130K9

Arrive LED lanterns feature a die-cast aluminum, powder coated frame and heavily textured glass. One-light extra-large wall lantern. 90+ CRI, 3000K, 1,211 lumens 71.2 lumens/watt per module (source). Energy Star.

Specifications:

Description:

- · Black (-31) (painted)
- Die-cast aluminum Construction
- Clear Seeded glass panels
- LED Module is replaceable (part # 93053641)
- Die-cast aluminum, powder coated frame.
- Heavily textured glass.
- 90+ CRI, 3000K, Energy Star.
- 1,211 lumens 71.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR[®] qualified
- Meets California Title 24 high efficacy requirements for outdoor use only

Performance:

| Number of Modules | 1 | Width: Depth: Height H/CTR |
|------------------------|--|-------------------------------------|
| Input Power | 17w | |
| Input Voltage | 120 V | |
| Input Frequency | 60 Hz | |
| Lumens/LPW (Source) | 1211/71.2 (LM-82) | |
| Lumens/LPW (Delivered) | 824/49.3 (LM-79) | Glass Width: Length Height |
| ССТ | 3000 K | |
| CRI | 90 CRI | |
| Life (hours) | 60,000 (L70/TM-21) | |
| FCC | Meets FCC Title 47, Part 15 Class B | |
| Min. Start Temp | -30 °C | |
| Max. Operating Temp | 30 °C | |
| Warranty | 5 year warranty | |
| Labels | cCSAus Wet location listed | |
| | ENERGY STAR [®] qualified | |
| | Meets California Title 24 high efficacy requirements | |
| | for outdoor use only | |



Dimensions:

Width: 11" Depth: 12-1/4" Height: 16" H/CTR: 8-5/8"

Glass Width: 0-1/8" Length: 7-5/8" Height: 11-5/16"



One-Light Outdoor

Wall mounted • Wet location listed PROGRESS LED



P6076-3130K9

Dimming Notes:

P6076 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.